



ARMOR GUYS
• PROTECTED •

CHEMIFLEX



Chemical Resistance

05-003 SPECIFICATION SHEET

FEATURES:

LINER

15 MIL, Flocked Liner
Unsupported

COATING

Green Nitrile Coating

BENEFITS:

Excellent Solvent Resistance

RANGE:

Chemiflex

APPLICATIONS:

Chemical Processing
Food Processing
Machining
Printing Press Operations
Oil & Gas
Petrochemicals

Armor Guys reference number : 05-003

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)



EN374-3



KLJ

EN388



3101

SPECIFICATIONS

COATING MATERIALS	Green Nitrile Coating
SIZES	XS-XXL

PACKAGING						
CASE SIZE	XS	S	M	L	XL	XXL
PER CARTON	144	144	144	144	144	144
CASE WEIGHT	17.40/lbs	18.06/lbs	18.72/lbs	19.82/lbs	20.93/lbs	21.59/lbs
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Light Blue
ORIGIN	PRC					

PERFORMANCE LEVEL

EN388: 3101						
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5