

BioClean-D™ Coverall with Hood and Integrated Boots -Sterile S-BDFC

Sterile cleanroom coverall with hood and integrated boots, for chemical and liquid splash protection

- Reduced contamination risks:
 Lightweight CleanTough™ material means the BioClean-D Coverall with Hood and Integrated Boots Sterile S-BDFC is low-linting and ISO cleanroom-compliant, reducing contamination risks
- Optimized protection: This sterile coverall features a front zip with a protective flap, resisting liquid splashes and chemicals*, while thumb loops and an elasticated hood, back, cuffs and ankles ensure a secure fit
- Enhanced features: This antistatic coverall features integrated boots and slip-resistant soles, for added workplace safety in laboratory settings
- Sterility assurance level: Special packaging eliminates cross contamination, while gamma irradiation sterilization ensures a minimum SAL of 10-6



Key Features and Benefits

- CleanTough[™] fabric: For a lightweight, low-linting sterile coverall
- Front zip and protective flap: Contaminant and liquid splash defenses
- Integrated boots and anti-slip soles: Head-to-toe personal protection

Industries

- Controlled and Critical Environments
- Production and Manufacturing
- Pharmaceutical Manufacturing
- Biotechnology Manufacturing
- Medical Device Manufacturing

WARDANISTIC RESONCH







BioClean-D™ Coverall with Hood and Integrated Boots -Sterile S-BDFC

TECHNICAL DATA SHEET

PRODUCT INFORMATION

Material	CleanTough™
Audit Standards	ISO 14001, Manufacturing QMS Audit Standards ISO 9001, PPE Regulation 2016 425 Module D, NEBB Certified Cleanrooms
Standards	ASTM F739, CE 0598, EN 13934-1, EN 13935-2, EN 6530, EN 7854, EN 863, EN 9073-4, EN ISO 13688:2013, ISO 11137-1:2006, EN ISO 14325, Category III, EN ISO 13982-1:2004 + A1:2010, EN 13034:2005 + A1:2009
	One piece aseptically folded per sealed inner PE bag; one inner bag per sealed outer PE bag; 20 outer bags per lined carton (20 pieces). Please note: sizes 3XL & 4XL 15 pieces per carton
Packaging Overview	More sustainable packaging: Packed in recyclable plastic packaging and delivered in recycled cardboard shipper cases. Inner and outer bags and liner are made from polyethylene (PE) based film. Always check your local recyclable status as these materials may not be considered suitable for recycling in your location.
Storage	Keep away from direct sunlight; store in a dry place and keep in the original packaging. Keep away from ozone sources. If products are properly stored, as indicated, they won't lose their performances or change characteristics significantly. If products could be affected by ageing or storage, the expiry date is mentioned on the packaging materials.*
Country Of Origin	China
Sterilization Method	GAMMA irradiation (25 kGy)
Sterilization Minimum Dose	25kGy
Sterility Assurance Level	10 ⁻⁶
Cleanroom Class	Class 10/ISO Class 4 & EU GMP Grade A/B and other sterile cleanrooms
Shelf Life	Three (3) years from the date of manufacture.
Construction	Seams joined with single-needle stitches
Characteristics	*NOTE: BioClean CleanTough material is static dissipative and, with a charge half decay time of 0.07 sec, and so are ideal for use in a static-safe environment.

PARTICLE SHEDDING TEST RESULTS

TEST	RESULT	
Particle Shedding (Helmke Drum Test)	≥ 0.5Qm (counts/min) <2000	

ASTM F739-12 TEST METHOD RESULTS

ASTITITOS IL TEST TIETTOS RESOLTO				
DRUG	Mean Breakthrough Time (MBT), Minutes Breakthrough of the test chemical is deemed to have occurred when the permeation rate has reached 0.1 Qg/cm² /min			
CISPLATIN	>240			
CARMUSTINE	<6			
CYCLOPHOSHAMIDE	217 (275,162,215)			
DOXORUBICINHYDROCHLORIDE	>240			
5-FLUOROURACIL	>240			
METHOTREXATE	>240			
ETOPOSIDE	>240			
PACLITAXEL	<10			
THIOTEPA	30 (28,30,33)			

Results achieved under controlled laboratory conditions, by accredited external testing laboratory. *For Bioclean D and Bioclean 2000, the chemical permeation results relates to the fabric performance for reference only. Seams and closures may have lower breakthrough times. We recommend garments with sealed seams such as Bioclean-C to be worn over the coverall for added protection against chemotherapy drugs handling.

SIZE CHART

S-BDFC-S Chest: 84-92cm (33"-36") Height: 164-170cm (5'4"-5'6") Size: S S-BDFC-M Chest: 92-100cm (36"-39") Height 170-176cm (5'6"-5'9") Size: M S-BDFC-L Chest: 100-108cm (39"-42") Height: 176-182cm (5'9"-6'0") Size: L S-BDFC-XL Chest: 108-116cm (42"-45") Height: 182-188cm (6'0"-6'2")Size: XL S-BDFC-2XL Chest: 116-124cm (45"-48") Height: 188-194cm (6'2"-6'4") Size: 2XL S-BDFC-3XL Chest: 124-132cm (48"-51") Height: 194-200cm (6'4"-6'6") Size: 3XL S-BDFC-4XL Chest: 132-140cm (51"-54") Height: 200-206cm (6'6"-6'8") Size: 4XL





BioClean-D™ Coverall with Hood and **Integrated Boots -**Sterile S-BDFC

MATERIAL PERFORMANCE TEST RESULTS

TEST	RESULT	PERFORMANCE CLASS	PERFORMANCE STANDARD
Abrasion Resistance	>10 cycles	1	EN 12947-2
Flex Cracking Resistance	>50,000 cycles	6	EN ISO 7854
Puncture Resistance	>5 N	1	ISO 13996
Trapezoidal Tear Resistance Cross Direction (CD)	>10 N	1	EN ISO 9073-4
Trapezoidal Tear Resistance Machine Direction (MD)	>10 N	1	EN ISO 9073-4
Tensile Strength Cross Direction (CD)	>30 N	1	EN ISO 13934-1
Tensile Strength Machine Direction (MD)	>30 N	1	EN ISO 13934-1
Repellence to Liquids - 30% H ₂ SO ₄	>90%	3	ISO 6530
Repellence to Liquids - 10% NaOH	>90%	3	ISO 6530
Repellence to Liquids - O-Xylene	>80%	2	ISO 6530
Repellence to Liquids - Butan-1-ol	>90%	3	ISO 6530
Penetration by Liquids - 30% H ₂ SO ₄	<1%	3	ISO 6530
Penetration by Liquids - 10% NaOH	<1%	3	ISO 6530
Penetration by Liquids - O-Xylene	<1%	3	ISO 6530
Penetration by Liquids - Butan-1-ol	<1%	3	ISO 6530
Inward leakage of aerosols of fine particles ¹	PASS	N/A	EN ISO 13982-2
Resistance to penetration by spray (Spray Test) ¹	PASS	N/A	IN ISO 17491-4
Seam Strength ²	>50 N	2 (Main Fabric)	ISO 13935-2
Electrostatic Charge Half Decay Time, t ₅₀ (secs)	PASS	N/A	EN1149-3

^{1.} All interfaces with additional PPE were taped during testing, as required by the standards.

ORDERING INFORMATION

	SIZE	S, M, L, XL,2XL	3XL, 4XL
S-BDFC	REORDER NO.	S-BDFC-S, S-BDFC-M, S- BDFC-L, S-BDFC-XL, S- BDFC-2XL	S-BDFC-3XL, S-BDFC-4XL

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890

Performance Standards and Regulatory Compliance












Ansell, @ and $^{\text{M}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking @ 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.





^{2.} Seam not destroyed., 3. The material is static dissipative. Tested in accordance with EN1149-5.