

36" & 48" Portable Evaporative Coolers



FRONT
Patented

15°F - 25°F OF EVAPORATIVE COOLING
- PLUS -
6°F - 8°F OF WIND CHILL COOLING

EVAPORATIVE COOLING TEMPERATURE DROPS			
AIR	RELATIVE HUMIDITY		
TEMPERATURE	10%	30%	50%
80°	-22°	-16°	-10°
90°	-25°	-18°	-12°
100°	-29°	-21°	-14°
110°	-32°	-23°	-15°



BACK
Patented

36" Single or Three Speed

48" Two Speed

(EVAP36-1 or EVAP36-3) provides cooling up to 2500 sq. ft. area. 32 Gallon reservoir capacity.

(EVAP48-2) provides cooling up to 4,000 sq. ft. area. 40 Gallon reservoir capacity.

36" UNIT IS THIN ENOUGH TO FIT THROUGH A STANDARD DOOR.

Features

- 36" and 48" non hazardous location models feature 3/4" garden hose connections for longer operating times
- Durable polyethylene housing features leakproof, one piece construction
- Lowers temperatures 15-25 °F depending on climate conditions
- Heavy duty, polyolefin casters on evaporative coolers
- New 3 blade fan blade for quieter operation
- 120V operation
- Manufactured in U.S.A. Shipped completely assembled, ready to use

Standard Models

UPC# 686334	MODEL	MOTOR HP	UNIT AMPS	CFM			EFFECTIVE SQ. FT.	INTERNAL WATER (Gallons)	DIMENSIONS L x W x H (Inches)	WT. (LBS.)	LIST
				HIGH	MED	LOW					
874816	EVAP36-1	1/2	12.4	9600			2500	32	32 x 62 x 67	235	4,120
874823	EVAP36-3	1/2	11.5	9600	6600	4800	2500	32	32 x 62 x 67	245	4,506
874847	EVAP48-2	1	13.7	22000	----	11000	4000	40	36 x 74 x 86	405	6,386

Hazardous Location - Standard Models



FRONT
Patented



CONTROL
Patented

Hazardous Location - Specific Features

- All switches, motors, and cord connections are sealed to prevent sparking in combustible locations
- Shipped completely assembled, ready to use
- 120/240V operation
- Manufactured in U.S.A.
- Component Rating: Class 1A, Division D for Hazardous Location

Hazardous Location - Standard Models

UPC# 686334	MODEL	MOTOR HP	UNIT AMPS	CFM			EFFECTIVE SQ. FT.	INTERNAL WATER (Gallons)	DIMENSIONS L x W x H (Inches)	WT. (LBS.)	LIST
				HIGH	MED	LOW					
874830	EVAP36-HAZ	1/2	13.4	9600			2500	32	32 x 62 x 67	330	13,312
874854	EVAP48-HAZ	1	18	20000			4000	40	36 x 74 x 86	460	16,109