

Busbar system Busbar center-to-center spacing 40 mm Device adapter, Width: 54 mm Bar thickness: 5+10 mm for equipping as required Outgoing unit top 16 mm² (32 A) without outgoing cable 1 mounting rail 35 mm Access bottom 35 mm² (80A)



Model	
Product brand name	SENTRON
Product designation	Device adapter
Design of the product	Accessories
Current / at AC / rated value	80 A
Operating voltage / at AC / rated value	690 V
Width	54 mm
Busbar center-to-center spacing	40 mm
Net weight	292 g

General Product Approval			Declaration of Conformity	Test Certificates	
 CSA	 UR		 EG-Konf.	Special Test Certificate	Miscellaneous

Shipping Approval	other
 PRS	 RINA
	Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1060-5AK00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8US1060-5AK00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1060-5AK00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

