

Nitrile disposable gloves specially designed to protect while minimizing Type IV skin allergies

- **Reduced allergy risk:** Clinically proven to reduce redness and itching associated with contact dermatitis and minimize Type IV allergy risks
- **Tactile sensitivity:** Thin and lightweight construction for greater tactility
- **Secure grip:** Textured fingertips for secure handling of tools & materials



Industries

- Life Sciences
- Healthcare

Recommended For

- Assembly of parts
- Sample taking and processing
- Protection from latex Type I allergy and minimize chemical Type IV allergies in HCW's or patients
- Standard patient examinations
- Helping protect skin from drying or cracking
- Protection from Type I latex allergy in HCW's or patients

TECHNICAL DATA SHEET

| Product Information | |
|-------------------------------|---|
| External Glove Surface | Textured Fingers |
| Audit Standards | ISO 13485:2003 |
| Product Certification | ASTM D6319, EN ISO 21420:2020, FDA21 CFR 177-2600-US Food Contact Approved, US QSR/FDA 510(k) Medical Examination Grade, EU Food Contact Approved |
| Packaging Overview | 100 gloves per dispenser 10 dispensers per case 1000 gloves per case |
| Storage Instructions | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin | Malaysia |
| Product Segmentation | High Touch |
| Antistatic | Yes |
| Silicone Free | No |

PHYSICAL PROPERTIES

| | Typical Values | Testing Method | |
|---|---------------------|---------------------|------------------|
| Length (mm/inches) | 240 / 9.5 | ASTM D3767,EN 420 | |
| Freedom from Holes (Inspection level I) | 1.5 AQL | ASTM D5151,EN 455-1 | |
| Palm Thickness (mm/mils) | 0.06 / 2.4 | ASTM D3767,EN 420 | |
| Finger Thickness (mm/mils) | 0.10 / 3.9 | ASTM D3767,EN 420 | |
| | BEFORE AGING | AFTER AGING | |
| Ultimate Tensile Strength (MPa) | 29 | 20 | ASTM D412 & D573 |
| Elongation at Break (%) | ≥ 500 | ≥ 400 | ASTM D3767 |

ORDERING INFORMATION

| Size | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|---------------------|--------------|-------------|-------------|-------------|---------------|
| Product Code | N730 | N731 | N732 | N733 | N734 |

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV

T: +32 (0) 2 528 74 00

F: +32 (0) 2 528 74 01

Asia Pacific Region

MY: +603 8310 6688

apac.medical@ansell.com

CN: +86 21 38275000

infochina@ansell.com

JP: +813 5549 8151

info.medical.jp@ansell.com

North America Region

Ansell Healthcare Products LLC

T: +1 800 800 0444

F: +1 800 800 0445

Latin America & Caribbean Region

BR: +55 (11) 3356-3100

latam.medical@ansell.com

MX: +52 442 296 2050

latam.medical@ansell.com

CO: +57 1 288 3247

latam.medical@ansell.com

Australia

Ansell Limited

T: +61 1800 337 041

F: +61 1800 803 578

Russia

Ansell PYC

Tel: +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

