



SPECIFICATION SHEET

151-2-18

NOVAX RUBBER INSULATING GLOVES: CLASS 2

- Meet ANSI/ASTM D120 standard and NFPA 70E for use around electrical hazards and arc flash protection.
- Contoured shape reduces hand fatigue.
- Natural rubber construction offers the required dielectric properties combined with flexibility, strength and durability.
- Silicone free.

APPLICATIONS

Used exclusively for electrical purposes, such as power generation, electrical contractors, hybrid automotive repair/service, hybrid automobile manufacturing, industrial plant maintenance, utilities.

MAX USE VOLTAGE

	SC V rms	DC V
CLASS 4	17,000	25,500


10 NOVAX™ by G.B. INDUSTRIES
ANSI / ASTM CLASS 2 MADE IN MALAYSIA D120 TYPE I
MAX USE VOLT 17000V AC

TECHNICAL DATA

SHELL	Natural Rubber
COLOR	Black/Yellow
CUFF STYLE	Contour, Rolled
SIZES	8-12
PACKAGING	1 pair per bag/box, 12 pair per case
CASE	21.8" x 8.7" x 3.8"
CASE WEIGHT	35.3 lbs / 16.0 kg
COO	Malaysia

BARCODES

ITEM	PAIR	CASE
■ 151-2-18/8	616314116896	02616314116894
■ 151-2-18/9	616314116902	02616314116900
■ 151-2-18/10	616314116865	02616314116863
■ 151-2-18/11	616314116872	02616314116870
■ 151-2-18/12	616314116889	02616314116887



DIMENSIONS (in/cm)

	8	9	10	11	12
A	18.0 / 45.7	18.0 / 45.7	18.0 / 45.7	18.0 / 45.7	18.0 / 45.7
B	3.9 / 10.0	4.1 / 10.5	4.7 / 12.0	5.3 / 13.5	15.0 / 5.9

Max Thickness: 2.29mm*

