



## 5-Gallon Tight-Head UN Rated Steel Drum

DRM683 5 gal., UN1A1/X1.6/250, 0.9/0.9/0.9 mm Thick

Tough, UN Rated drums are made for hazardous materials, so you can rely on them to deliver safety and compliance.

- UN Rated and tested to help ensure safe shipping of hazardous materials
- Tight-head design is equipped with 2" NPT and 3/4" NPT bungs
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance
- 20-gauge steel top, body and bottom meet strict wall thickness requirements to ensure strength, durability and long life

Item#	Description	Dimensions	Weight
DRM683-ULD	Unlined	ext. dia. 14.5" x 11.25" H	10 lbs.
DRM683-LD	Lined	ext. dia. 14.5" x 11.25" H	10 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM683-ULD	Unlined	ext. dia. 36.8cm x 28.6cm H	4.5 kg
DRM683-LD	Lined	ext. dia. 36.8cm x 28.6cm H	4.5 kg

### Specifications

<b>Drum Lid Closure</b>	Tight-Head
<b>Container Type</b>	Drums & Barrels
<b>Lining</b>	Lined; Unlined
<b>Size</b>	5 gal.
<b>Thickness</b>	0.9/0.9/0.9 mm Thick
<b>Color</b>	Black/White
<b>Dimensions</b>	ext. dia. 14.5" x 11.25" H
<b>Storage Capacity</b>	5 gal.
<b>Bung Type</b>	2" NPT and .75" NPT (Tri-Sure) Bungs
<b>Drum Type</b>	Steel Drum
<b>Interior Dimensions</b>	14" Dia. x 10.75" H Interior
<b>Lid Type</b>	Tight-Head
<b>Sold as</b>	1 each
<b>Weight</b>	10 lbs.

# per Pallet	45
Composition	Drum - Steel Bung Gasket - Buna-N Lining - Phenolic Epoxy
UNSPSC	24112108
Pigalog® Page Number	<u>Page 315</u>
<b>Metric Equivalent</b>	
Dimensions	ext. dia. 36.8cm x 28.6cm H
Storage Capacity	18.9 L
Weight	4.5 kg

## Technical Information

### Certifications, Approvals and Ratings

UN1A1/X1.6/250



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)