WILLIAMS





3/4" DRIVE SHALLOW IMPACT SOCKETS, 6 POINT, SAE

Black Industrial Finish

		A	D		г		
			Drive End	Working End	Nose	Uses	
Product	Size	OAL	Diameter	Diameter	Length	RET RING®	Use
Code	(Inches)	(Inches)	(Inches)	(Inches)	(Inches)	Number	O-Ring / Pin
38118	9/16	2	1 ⁵ /8	1	1	6-1XS	6-1A / 6-2B
38120	5/8	2	1 5/8	1 3/32	1	6-1XS	6-1A / 6-2B
38122	11/16	2	1 1/8	1 5/32	1	6-1XS	6-1A / 6-2B
38124	3/4	2	1 5/8	1 1/4	1	6-1XS	6-1A / 6-2B
38126	13/16	2	1 1/8	1 5/8	1	6-1XS	6-1A / 6-2B
38128	7/8	2	1 11/16	17/16	2 %16	6-1XS	6-1A / 6-2B
38130	15/16	2	1 11/16	1 1/2	2 %16	6-1XS	6-1A / 6-2B
38132	1	2 1/16	1 ¹¹ / ₁₆	1 %16	5/8	6-1XS	6-1A / 6-2B
38134	1 1/16	2 1/16	1 ¹¹ / ₁₆	1 11/16	25/32	6-1XS	6-1A / 6-2B
38136	1 1/8	2 1/16	1 3/4	1 3/4	25/32	6-1XS	6-1A / 6-2C
38138	1 3/16	2 1/16	1 3/4	1 ¹³ / ₁₆	25/32	6-1XS	6-1A / 6-2C
38140	1 1/4	2 1/4	1 3/4	1 1/8	13/16	6-1XS	6-1A / 6-2C
38142	1 5/16	2 1/4	1 3/4	1 ¹⁵ / ₁₆	13/16	6-1XS	6-1A / 6-2C
38144	1 3/8	2 1/4	1 3/4	2 1/16	13/16	6-1XS	6-1A / 6-2C
38146	1 7/16	2 1/4	1 3/4	2 ⁷ / ₆₄	13/16	6-1XS	6-1A / 6-2C
38148	1 1/2	2 1/4	1 3/4	2 ¹³ / ₆₄	7/8	6-1XS	6-1A / 6-2C
38150	1 %16	2 1/4	1 3/4	2 ⁷ / ₃₂	7/8	6-1XS	6-1A / 6-2C
38152	1 5/8	2 1/4	1 3/4	2 15/64	7/8	6-1XS	6-1A / 6-2C
38154	1 11/16	2 7/16	1 3/4	2 15/32	1	6-1XS	6-1A / 6-2C
38156	1 3/4	2 7/16	1 3/4	2 1/2	1	6-1XS	6-1A / 6-2C
38158	1 ¹³ / ₁₆	2 ⁷ / ₁₆	1 3/4	2 ¹⁹ / ₃₂	1	6-1XS	6-1A / 6-2C
38160	1 7/8	2 11/16	1 3/4	2 ¹¹ / ₁₆	1 3/16	6-1XS	6-1A / 6-2C
38162	1 ¹⁵ / ₁₆	2 11/16	1 3/4	2 ³ / ₄	1 3/16	6-1XS	6-1A / 6-2C
38164	2	2 11/16	1 3/4	2 ¹³ / ₁₆	1 3/16	6-1XS	6-1A / 6-2C

Fed. Spec: ANSI B107.2

38920 9 Piece 3/4" Drive Shallow 6 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
38132	1	38138	1 ³ / ₁₆	38144	1 %
38134	1 1/16	38140	1 1/4	38146	1 7/16
38136	1 1/8	38142	1 ⁵ ⁄16	38148	1 ½

38901 16 Piece 3/4" Drive Shallow 6 Point Impact Socket Set with 50083 Metal Box

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
38128	7/8	38140	1 1/4	38156	1 3/4
38130	¹⁵ / ₁₆	38142	1 5/16	38158	1 ¹³ / ₁₆
38132	1	38144	1 %	38160	1 1/8
38134	1 1/16	38146	1 7/16	38164	2
38136	1 1/8	38148	1 1/2		
38138	1 3/16	38152	1 %		

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.
- Suitable for use with pneumatic and electric impact wrenches.
- · Specially heat treated for impact use to provide long life, safety, and durability.
- · Drive end features pin retention hole and groove.







