

3/8" DRIVE DEEP SOCKETS, 6 POINT, METRIC

High-Polished Chrome Finish

Product Code	Size (MM)	A OAL (Inches)	B Drive End Diameter (Inches)	C Working End Diameter (Inches)	D Broach Depth (Inches)	E Bolt Clearance Depth (Inches)	F Bolt Clearance Diameter (Inches)	Nose Length (Inches)
BMD-606	6	2 1/8	1 1/16	13/32	7/32	1 11/16	7/32	1 5/8
BMD-607	7	2 1/8	1 1/16	13/32	9/32	1 11/16	1/4	1 5/8
BMD-608	8	2 1/8	1 1/16	15/32	9/32	1 11/16	9/16	1 5/8
BMD-609	9	2 1/8	1 1/16	1/2	9/32	1 11/16	11/32	1 5/8
BMD-610	10	2 1/8	1 1/16	9/16	5/16	1 11/16	3/8	1 5/8
BMD-611	11	2 1/8	1 1/16	5/8	3/8	1 11/16	7/16	1 5/8
BMD-612	12	2 1/8	1 1/16	21/32	13/32	1 11/16	15/32	1 5/8
BMD-613	13	2 1/8	23/32	23/32	13/32	1 5/8	17/32	-
BMD-614	14	2 3/8	25/32	25/32	13/32	1 9/16	17/32	-
BMD-615	15	2 3/8	19/16	13/16	13/32	1 9/16	17/32	-
BMD-616	16	2 3/8	27/32	27/32	13/32	1 9/16	19/32	-
BMD-617	17	2 21/32	29/32	29/32	1/2	1 13/16	5/8	-
BMD-618	18	2 21/32	31/32	31/32	1/2	1 13/16	21/32	-
BMD-619	19	2 21/32	1	1	5/8	1 15/16	23/32	-
BMD-620	20	2 21/32	1 1/32	1 1/32	5/8	1 15/16	23/32	-
BMD-622	22	2 7/8	1 5/16	1 5/16	5/8	2 5/32	7/8	-
BMD-623	23	2 7/8	1 3/16	1 3/16	1/2	2 5/32	27/32	-
BMD-624	24	2 7/8	1 1/4	1 1/4	9/16	2 5/32	15/16	-
BMD-625	25	2 7/8	1 9/32	1 9/32	9/16	2 1/8	31/32	-

Fed. Spec: ANSI B107.110



BMD-612 BMD-606

MSBD-12HRC 12 Piece 3/8" Drive Deep 6 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)
BMD-608	8	BMD-612	12	BMD-616	16
BMD-609	9	BMD-613	13	BMD-617	17
BMD-610	10	BMD-614	14	BMD-618	18
BMD-611	11	BMD-615	15	BMD-619	19

MSBD-19HRC 19 Piece 3/8" Drive Deep 6 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)
BMD-606	6	BMD-611	11	BMD-616	16	BMD-622	22
BMD-607	7	BMD-612	12	BMD-617	17	BMD-623	23
BMD-608	8	BMD-613	13	BMD-618	18	BMD-624	24
BMD-609	9	BMD-614	14	BMD-619	19	BMD-625	25
BMD-610	10	BMD-615	15	BMD-620	20		

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.



Made in U.S.A.



MSBD-12HRC



MSBD-19HRC