

SOCKETS & DRIVE TOOLS

1/2" DRIVE

Snap-on INDUSTRIAL BRANDS

WILLIAMS



1/2" DRIVE SHALLOW SOCKETS, 6 POINT, SAE

High-Polished Chrome Finish

Product Code	Size (Inches)	A OAL (Inches)	B Drive End Diameter (Inches)	C Working End Diameter (Inches)	D Broach Depth (Inches)	E Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	F Nose Length (Inches)
ST-612	3/8	1 1/2	29/32	19/32	5/16	7/8	11/32	23/32
ST-614	7/16	1 1/2	29/32	21/32	3/8	7/8	13/32	23/32
ST-616	1/2	1 1/2	29/32	3/4	3/8	7/8	15/32	23/32
ST-618	9/16	1 1/2	29/32	13/16	3/8	7/8	15/32	23/32
ST-619	19/32	1 1/2	29/32	7/8	3/8	7/8	15/32	23/32
ST-620	5/8	1 1/2	29/32	29/32	9/16	7/8	15/32	-
ST-622	11/16	1 1/2	31/32	31/32	19/16	27/32	5/8	-
ST-624	3/4	1 1/2	1 1/32	1 1/32	19/16	27/32	23/32	-
ST-625	25/32	1 1/2	1 1/16	1 1/16	19/16	27/32	3/4	-
ST-626	13/16	1 1/2	1 1/8	1 1/8	19/16	27/32	25/32	-
ST-628	7/8	1 1/2	1 3/16	1 3/16	19/16	13/16	7/8	-
ST-630	15/16	1 17/32	1 9/32	1 9/32	19/16	27/32	29/32	-
ST-632	1	1 9/16	1 11/32	1 11/32	27/32	7/8	31/32	-
ST-634	1 1/16	1 11/16	1 7/16	1 7/16	31/32	1	1 1/16	-
ST-636	1 1/8	1 3/4	1 1/2	1 1/2	1 1/32	1 1/16	1 1/8	-
ST-640	1 1/4	1 7/8	1 11/16	1 11/16	1 1/8	1 5/32	1 1/4	-

Fed. Spec: ANSI B107.1

WSS-14HRC 14 Piece 1/2" Drive Shallow 6 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
ST-612	3/8	ST-622	11/16	ST-632	1
ST-614	7/16	ST-624	3/4	ST-634	1 1/16
ST-616	1/2	ST-626	13/16	ST-636	1 1/8
ST-618	9/16	ST-628	7/8	ST-640	1 1/4
ST-620	5/8	ST-630	15/16		

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.



WSS-14HRC

