



WS-7-19TB



1" DRIVE SHALLOW IMPACT SOCKETS, 6 POINT, SAE

WS-7-19TB 19 Piece 1" Drive Shallow 6 Point Impact Socket Set in Tool Box Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
7-648	1 1/2	7-676	2 3/8	7-6100	3 1/8
7-652	1 5/8	7-680	2 1/2	7-6104	3 1/4
7-656	1 3/4	7-682	2 9/16	7-6112	3 1/2
7-660	1 7/8	7-684	2 5/8	7-107	7 3/8" EXT
7-664	2	7-688	2 3/4	7-140B	U-JOINT
7-668	2 1/8	7-692	2 7/8	TB-6124A	TOOL BOX
7-672	2 1/4	7-696	3		

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.
- Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.



1" DRIVE SHALLOW IMPACT SOCKETS, 12 POINT, SAE


Black Industrial Finish

TOOLS @ HEIGHT
DROP PREVENTION SYSTEM

Side hole in socket permits use with Snap-on Industrial Brands Tools@Height drive tools such as ratchets, extensions and u-joints



39720



Product Code	Size (Inches)	A							F
		Overall Length (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Diameter (Inches)	Nose Length (Inches)	
39720	5/8	2 1/4	2	1 3/16	7/16	/	/	1	
39724	3/4	2 1/4	2	1 1/2	7/16	/	/	1	
39726	13/16	2 1/4	2	1 1/2	7/16	/	/	1	
39728	7/8	2 1/4	2	1 1/2	1/2	/	/	1	
39730	15/16	2 1/4	2	1 1/2	1/2	/	/	1	
39732	1	2 1/4	2	1 5/8	1/2	/	/	1	
39734	1 1/16	2 1/4	2	1 3/4	1/2	/	/	1	
39736	1 1/8	2 1/4	2	1 3/4	5/8	/	/	1	
39738	1 3/16	2 7/16	2	1 7/8	5/8	/	/	1 1/8	
39740	1 1/4	2 7/16	2	2	5/8	/	/	/	
39742	1 5/16	2 7/16	2 1/16	2 1/8	3/4	/	/	1 3/16	
39744	1 3/8	2 7/16	2 1/16	2 1/8	3/4	/	/	1 3/16	
39746	1 7/16	2 7/16	2 1/16	2 1/4	3/4	/	/	1 3/16	
39748	1 1/2	2 7/16	2 1/16	2 1/4	7/8	/	/	1 3/16	
39750	1 9/16	2 7/16	2 1/16	2 1/4	7/8	/	/	1 3/16	
39752	1 5/8	2 7/16	2 1/16	2 1/4	7/8	/	/	1 3/16	
39754	1 11/16	2 1/2	2 1/16	2 1/2	1	/	/	1 3/16	
39756	1 3/4	2 1/2	2 1/4	2 1/2	1	/	/	1 3/16	
39758	1 13/16	2 1/2	2 1/4	2 5/8	1	/	/	1 3/16	
39760	1 7/8	2 1/2	2 1/4	2 3/4	1 1/16	/	/	1 3/16	
39762	1 15/16	2 5/8	2 1/4	2 3/4	1 1/16	/	/	1 3/16	
39764	2	2 3/4	2 1/4	2 5/16	1 1/16	/	/	1 3/16	
39766	2 1/16	2 3/4	2 1/4	2 5/16	1 3/16	/	/	1 3/16	
39768	2 1/8	2 3/4	2 1/4	3 1/16	1 3/16	/	/	1 3/16	
39770	2 3/16	2 3/4	2 7/16	3 3/16	1 3/16	/	/	1 3/16	
39772	2 1/4	2 15/16	2 7/16	3 1/4	1 1/4	/	/	1 3/16	
39776	2 3/8	3 1/16	2 7/16	3 1/2	1 3/8	/	/	1 3/16	
39780	2 1/2	3 3/16	2 7/16	3 1/2	1 3/8	/	/	1 3/16	
39782	2 9/16	3 3/16	2 7/16	3 5/8	1 3/8	/	/	1 3/16	
39788	2 3/4	3 3/8	2 7/16	3 7/8	1 1/2	/	/	1 1/4	
39794	2 15/16	3 3/4	3 3/8	4 1/8	1 5/8	/	/	1 1/2	
39796	3	3 3/4	3 3/8	4 1/8	1 5/8	/	/	1 1/2	

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 and 12 point fasteners.
- Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.

