



3/8" DRIVE SHALLOW SOCKETS, 6 POINT, SAE

High-Polished Chrome Finish



Product Code	Size (Inches)	A OAL (Inches)	B Drive End Diameter (Inches)	C Working End Diameter (Inches)	D Broach Depth (Inches)	E Bolt Clearance Depth (Inches)	F Nose Length (Inches)
B-608	1/4	1 1/32	11/16	13/32	7/32	9/16	1/2
B-610	5/16	1 1/32	11/16	7/16	1/4	9/16	1/2
B-611	11/32	1 1/32	11/16	1/2	9/32	9/16	1/2
B-612	3/8	1 1/32	11/16	9/16	9/32	9/16	1/2
B-614	7/16	1 1/32	11/16	5/8	5/16	9/16	1/2
B-616	1/2	1 1/32	23/32	23/32	11/32	9/16	-
B-618	9/16	1 3/32	25/32	25/32	9/16	19/32	-
B-620	5/8	1 1/8	27/32	27/32	19/32	5/8	-
B-622	11/16	1 5/32	19/16	15/16	5/8	5/8	-
B-624	3/4	1 3/16	1	1	21/32	11/16	-
B-626	13/16	1 1/4	1 1/16	1 1/16	11/16	23/32	-
B-628	7/8	1 9/32	1 5/16	1 5/16	3/4	25/32	-
B-630	15/16	1 3/8	1 1/4	1 1/4	13/16	27/32	-
B-632	1	1 13/32	1 5/16	1 5/16	27/32	7/8	-

Fed. Spec: ANSI B107.110

WSS-8HRC 8 Piece 3/8" Drive Shallow 6 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
B-608	1/4	B-614	7/16	B-620	5/8
B-610	5/16	B-616	1/2	B-624	3/4
B-612	3/8	B-618	9/16		

WSB-10HRC 10 Piece 3/8" Drive Shallow 6 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
B-610	5/16	B-618	9/16	B-626	13/16
B-612	3/8	B-620	5/8	B-628	7/8
B-614	7/16	B-622	11/16		
B-616	1/2	B-624	3/4		

WSB-13HRC 13 Piece 3/8" Drive Shallow 6 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
B-608	1/4	B-618	9/16	B-628	7/8
B-610	5/16	B-620	5/8	B-630	15/16
B-612	3/8	B-622	11/16	B-632	1
B-614	7/16	B-624	3/4		
B-616	1/2	B-626	13/16		

Features

- SUPERTORQUE[®] lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.



WSS-8HRC



WSB-10HRC



WSB-13HRC

3/8" DRIVE

SOCKETS AND
DRIVE TOOLS