



1/4" DRIVE DEEP SOCKETS, 6 POINT, SAE

High-Polished Chrome Finish



		A	B	C	D	F
Product Code	Size (Inches)	OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Diameter (Inches)
MD-605	5/32	2	15/32	9/32	5/32	5/32
MD-606	3/16	2	15/32	5/16	3/16	3/16
MD-607	7/32	2	15/32	11/32	7/32	7/32
MD-608	1/4	2	15/32	3/8	7/32	7/32
MD-609	9/32	2	15/32	13/32	1/4	9/32
MD-610	5/16	2	15/32	7/16	9/32	9/32
MD-611	11/32	2	1/2	1/2	9/32	11/32
MD-612	3/8	2	17/32	17/32	9/32	3/8
MD-614	7/16	2	19/32	19/32	3/8	19/32
MD-616	1/2	2	11/16	11/16	3/8	19/32
MD-618	9/16	2	3/4	3/4	3/8	17/32

Fed. Spec: ANSI B107.110

WSMD-10HRC 10 Piece 1/4" Drive Deep 6 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
MD-606	3/16	MD-609	9/32	MD-612	3/8
MD-607	7/32	MD-610	5/16	MD-614	7/16
MD-608	1/4	MD-611	11/32	MD-616	1/2
				MD-618	9/16

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.



1/4" DRIVE DEEP SOCKETS, 12 POINT, SAE

High-Polished Chrome Finish



		A	B	C	D	E	F
Product Code	Size (Inches)	OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)
30406	3/16	1 31/32	15/32	5/16	5/16	1 5/16	1/8
30407	7/32	1 31/32	15/32	11/32	3/8	1 9/16	9/16
30408	1/4	1 31/32	15/32	7/16	13/16	1 11/32	7/32
30409	9/32	1 31/32	15/32	7/16	25/32	1 11/32	1/4
30410	5/16	1 31/32	15/32	15/32	13/16	1 5/16	9/32
30411	11/32	1 31/32	1/2	1/2	23/32	1 5/16	5/32
30412	3/8	1 31/32	9/16	9/16	7/8	1 11/32	5/16
30414	7/16	1 31/32	5/8	5/8	7/8	1 1/2	13/32
30416	1/2	1 31/32	11/16	11/16	27/32	1 17/32	7/16
30418	9/16	1 31/32	3/4	3/4	29/32	1 9/16	17/32

Fed. Spec: ANSI B107.110

30937 10 Piece 1/4" Drive Deep 12 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
30406	3/16	30409	9/32	30412	3/8
30407	7/32	30410	5/16	30414	7/16
30408	1/4	30411	11/32	30416	1/2
				30418	9/16

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 12 point fasteners.